Inventor: Hur, Yoon-Seok

Reply to Office Action of April 3, 2007

**Amendments to the Claims:** 

This listing of claims will replace all prior versions, and listings, of claims in the

application.

**Listing of Claims:** 

1. (Currently amended) A circular stapler comprising:

a detachable anvil;

a head section coupled to the detachable the anvil and having a head section cover;

a cylindrical body that longitudinally extends, one end of the cylindrical body is coupled

to the head section by a transition section;

an axis extending through a center of the detachable anvil and a center of the cylindrical

body; and

wherein a recessed portion in a side surface of the transition section eylindrical body is

positioned proximate to under-the head section cover such that a distance from the axis to the

recessed portion is less than a distance from the axis to the cylindrical body and wherein the

recessed portion is adapted to receive an inner portion of an intestine.

2. (Original) The circular stapler according to claim 1, wherein the head section

cover has a circular plate shape.

(Original) The circular stapler according to claim 2, wherein the head section

comprises:

3.

a cylindrical blade;

-2-

Inventor: Hur, Yoon-Seok

Reply to Office Action of April 3, 2007

a staple holder having a plurality of staple slots which surround the outer circumferential

portion of the cylindrical blade, staples being provided inside the staple slots;

a push member provided with a protruded portion inserted into the staple slots for

pushing the staples; and

a support positioned under the push member and having a circular plate-shaped top for

pushing the push member.

4. (Original) The circular stapler according to claim 3, wherein the push member has

a circular plate-shaped housing and the protruded portion is formed on the circular plate-shaped

housing.

5. (Original) The circular stapler according to claim 3, wherein the push member is

coupled integrally to the support.

6. (Original) The circular stapler according to claim 3, wherein the circular plate-

shaped top is made of steel.

7. (Previously presented) The circular stapler according to claim 1, wherein the

length of the head section cover in a longitudinal direction of the cylindrical body is set to 15

through 18 mm.

-3-

Inventor: Hur, Yoon-Seok

Reply to Office Action of April 3, 2007

8. (Original) The circular stapler according to claim 1, wherein the cylindrical body has an arch shape.

9. (Original) The circular stapler according to claim 1, further comprising a detachable cap which is coupled and fixed to the recessed portion.

10. (Original) The circular stapler according to claim 1, further comprising a shaft which passes through the head section and the cylindrical body and extends long, wherein the diameter of the shaft is set to 1.0 through 1.5 mm.

11. (Original) The circular stapler according to claim 1, further comprising a trigger which is provided at a lower portion of the cylindrical body to oppose the recessed portion and which pushes the support.

- 12. (Previously presented) The circular stapler according to claim 1, wherein the recessed portion in the side surface of the cylindrical body is further positioned to receive the circumferential length of at least one tubular tissue.
- 13. (Previously presented) The circular stapler according to claim 1 further comprising means for anastomosing at least two tubular tissue sections connected end to end.

Inventor: Hur, Yoon-Seok

Reply to Office Action of April 3, 2007

14. (Previously presented) The circular stapler according to claim 1 further comprising means for anastomosing at least two tubular tissue sections connected end to side.

15. (Currently amended) A surgical stapler comprising:

a detachable anvil;

a head section coupled to the detachable the anvil and having a head section cover;

a cylindrical body that longitudinally extends, one end of the cylindrical body is coupled

to the head section by a transition section;

a cylindrical blade;

a staple holder having a plurality of staple slots which surround the outer circumferential

portion of the cylindrical blade, staples being provided inside the staple slots;

a push member provided with a protruded portion inserted into the staple slots for

pushing the staples;

a support positioned under the push member and having a circular plate-shaped top for

pushing the push member;

an axis extending through a center of the detachable anvil and a center of the cylindrical

body;

wherein a recessed portion in a side surface of the transition sectioneylindrical body is

positioned proximate to<del>under</del> the head section cover such that a distance from the axis to the

recessed portion is less than a distance from the axis to the cylindrical body, wherein the

recessed portion is adapted to receive an inner portion of an intestine, wherein the length of the

-5-

Inventor: Hur, Yoon-Seok

Reply to Office Action of April 3, 2007

head section cover in a longitudinal direction of the cylindrical body is in a range from less than about 15mm to 18 mm.

16. (Previously presented) The surgical stapler according to claim 15 further comprising a detachable cap which is coupled and releasably fixed to the recessed portion.

17. (Previously presented) The circular stapler according to claim 15, wherein the recessed portion in the side surface of the cylindrical body is further positioned to receive the circumferential length of at least one tubular tissue.

18. (Previously presented) The circular stapler according to claim 15 further comprising means for anastomosing at least two tubular tissue sections connected end to end.

19. (Previously presented) The circular stapler according to claim 15 further comprising means for anastomosing at least two tubular tissue sections connected end to side.

-6-